
ECONOCUT GANTRY TABLE MODEL: ECONOCUT 4000/POWERMAX 105

TECHNICAL DATA:	ECONOCUT
Power Voltage:	220V/380V 50HZ
Effective Cutting Width (mm):	3200
Effective Cutting Length (mm):	12000
the Disctance of rail (mm)	4000
The Length of rail(mm)	14000
Torch up-down moving distance (mm)	170mm
Idle max Cutting speed (mm/min)	12000mm/min
Flame cutting torch (Pcs)	1
Max flame cutting tickness	6-120mm
Plasma cutting torch (Pcs)	by powermax105
Plasma cutting thickness	dross free: 14mm pierce: 19mm







	pierce. 19iiiiii	
Critical component and benefets		
Plasma power source	Hypertherm powermax105	
Motor system	Panasonic motor	
Rail	24kg specification	
Driving system	Dual drive	
Flame torch and gas valve regulator assembly	China local brand, good quality	
Flame torch auto inigation	With auto fire inigation	
Automatic THC for flame	With Chinese local brand, capacitor type, good quality.	
CNC controller	HG616 CNC controller, 10" monitor	
Voltage stabilizer	supplied with. To make power input into controller and electronic stable	
Nesting software	NestinFastCAM software (professional) from Australia	
Packing Type	steel plate and vaccum package	

HUGONG WELDERS

شركة الاروزا بينوان و المعدان العديدية ذرير . TOLL FREE: 800 527672



Powermax105

Consumables



Mechanized shielded with ohmic 105 A consumables





retaining cap







Mechanized shielded with ohmic 45 Δ, 65 Δ, 85 Δ consumables









220994 Swirl ring

Mechanized unshielded 105 A consumables






Nozzle





Swirl ring















FineCut® shielded consumables







220842



Mechanized shielded with ohmic 105 A consumables Mechanized shielded with ohmic 45 A,65 A, 85 A consumables Mechanized unshielded 105 A consumables

Mechanized unshielded 45 A,65 A, 85 A consumables

FineCut Shielded consumables

Part number	Description
059476*	Powermax6
059477*	Powermax6

059478*

059479*	Powermax65/85/105 180° fu ll-l e
059480*	Powermax65/85/105 180° full-le
228737	Kit: Powermax65/85/105 180° fo
228738	Kit: Powermax65/85/105 180° fo
228735	Kit: Powermax65/85/105 180° fo
228736	Kit: Powermax65/85/105 180° fo

35/85/105 180° full-length machine torch assembly with 4.6 m (15 ft) lead 35/85/105 180° full-length machine torch assembly with 7.6 m (25 ft) lead Powermax65/85/105 180° full-length machine torch assembly with 10.7 m (35 ft) lead ength machine torch assembly with 15.2 m (50 ft) lead ength machine torch assembly with 22.9 m (75 ft) lead ull-length machine torch/MRT positioning sleeve

ull-length machine torch/MRT removable gear rack replacement ull-length/mini machine torch/MRT front mounting sleeve iull-length/mini machine torch/MRT adapter ring (coupler) Kit: Powermax65/85/105 180° full-length/mini machine torch main body replacement

228716 228720 Kit: Powermax65/85/105 180° full-length/mini machine torch/MRT cap-sensor switch replacement 058519 O-rina

075504 Pilot terminal screw

228730 Kit: Powermax65/85/105 180° full-length/mini machine torch lead replacement, 4.6 m (15 ft) Kit: Powermax65/85/105 180° full-length/mini machine torch lead replacement, 7.6 m (25 ft) 228731 Kit: Powermax65/85/105 180° full-length/mini machine torch lead replacement, 10.7 m (35 ft) 228732 Kit: Powermax65/85/105 180° full-length/mini machine torch lead replacement, 15.2 m (50 ft) 228733

228734 Kit: Powermax65/85/105 180° full-length/mini machine torch lead replacement, 22.9 m (75 ft) 228314 Kit: Powermax45/65/85/105 torch quick disconnect repair (latch & spring)







للأدرات و المعدات الحديدية ق. م. م TOLL FREE: 800 527672