



LAROSA
Hardware & Equip. Co. L.L.C
Machinery Consultant & Supplier Since 1996

(+971) 6 543 0053
sales@larosagroup.com
www.larosagroup.com

Industrial Area 2,
P.O Box : 41007,
Sharjah-U.A.E

SHARPENING MACHINE WITH SETTING MACHINE - PHASE 220V; 50Hz MODEL : TL - 60

Sharpening Circular Saws Blades

Teeth Profile	:	Triangular
Circular Saws Blades Thickness [min-max]	:	0.5 - 3 mm
Circular Saws Blade Inside Diameter [min-max]	:	20 - 50 mm
Circular Saws Blade Outside Diameter [min-max]:	:	110 - 550 mm
Sharpening Pitch [min-max]	:	5 - 15 mm
Sharpening Speed [teeth / minute]	:	33

Sharpening Bandsaw Blades

Teeth Profile	:	Triangular
Bandsaw Thickness [min-max]	:	0.5 - 1.5 mm
Bandsaw Width (min/max)	:	10-60mm
Sharpening Pitch (min/max)	:	15-16mm
Sharpening Speed (teeth/min)	:	33

Setting Bandsaw Blades

Characteristic

Motors Power: n° 2 x 0.18 kW
Motors Power: n° 1 x 0.09 kW
Wheel Grinder Dim.[Ø Ext x Int x Thickness]: 150x 20x6
Net - Gross Weight: 67 - 124 kg Machine
Dimensions [H x W x D]: ±260x 82 x 70 cm
Packing Dimensions [H x W x D]: 171 x 92 x 81 cm



VISCAT FULGOR



شركة لاروزا
للأدوات و المعدات الحديدية ذ . م . م

TOLL FREE : 800 527672