## **CNC TABLE PLASMA MACHINE C/W POWERMAX 125**

Model: FLASHCUT/POWERMAX125



TECHNICAL DATA:	
Machine color	Baileigh color
Power Voltage:	220V/380V, 50HZ
Effective Cutting Width (mm):	1500
Rail width(mm)	1800
Effective Cutting Length (mm):	3000
Rail length(mm)	3500
Torch up-down moving distance (mm)	170
Idle max Cutting speed (mm/min)	12000
Plasma cutting torch(pcs)	1
Cutting thickness(mm)	Due to plasma

Critical component and benefits	
Plasma power source	POWERMAX 125
servo motor	Panasonic motor
Driving system	dual driving, with 2 panasonic driving motor
Gear box	Gear box, ten years no need maintenance
Rail	HIWIN or TBI brand, Liner rails on X and Y
metal plate presser	supplied with
Automatic THC for plasma	Hugong ARC voltage THC, built-in HG613
CNC controller	Hugong HG613, 17" monitor
Dust removing	waterpool
Important Note	Buyer is responsible to arrange air dry to Plasma Machine to ensure the quality cutting and long time work. (COMPRESSOR+DRYER+FILTER)

HUGONG WELDERS

Main Part B rand			
Part name	Brand name	Logo	Origin
CNC controller	Amrican-Hypertherm	Homes the same	USA
Plasma unit	Amrican-Hypertherm	nyperinerm	USA
Torch height controller	Hugong	FastCAM*	China
Nesting software	Australian FastCAM		Australia
Servo motor-on Y axis	Japanese-Panasonic		Made in China
Servo motor-on X axis	Japanese-Panasonic	Domesonia	Made in China
Servo motor-on Z axis	Japanese-Panasonic	Panasonic	Made in China
Relay	Japanese-OMRON	OMRON.	Made in China
Breaker	French-Schneider	Schneider Electric	Made in China
Linear rail	HIWIN		Taiwan
alternative	ТВІ	HIWIN.	

## Hypertherm<sup>®</sup>

## Powermax125

Professional-grade plasma metal cutting and gouging system for handheld cutting 38 mm and mechanized piercing 25 mm.

Capacity	Thickness	Cut speed	
	Cutting		
Recommended	l38 mm	457 mm/min	
	44 mm	250 mm/min	
Severance (hand cutting)	57 mm	125 mm/min	
Pierce*	25 mm		
÷	Pierce rating for handheld use or w	vith automatic torch height control	-
Capacity	Metal removal rate	Groove profile*	

Gouging Typical gouge 12,52 kg/hr 4,3 mm-7,9 mm D x 6,1 mm-9,9 mm W

\*Actual groove profile varies with torch angle, arc stretch, and technique



**HUGONG** WELDERS

شركة الاروزا للفوات و المعدات العديدية ذ.م.م TOLL FREE: 800 527672