



HYDRAULIC PRESS BRAKE MACHINE

Model: W67Y - Series



Major Elements:

- NC Controller : E21 ESTUN
- Beide Motor : Seimens – China
- Electrical Components : Schneider
- Time Relay : Zhengtai
- Inverter for back gauge for Press brake : Delta
- Valve : Rexroth
- Seal : NOK
- Cast Chip-Sleeve-Connection : Italy
- CE Standard (including power off protection)
- Ball screw for back gauge, photoelectric protection, quick change clamping, standard upper & bottom tooling



Technical Parameters

Model WC67Y	Nominal Force (KN)	Length of worktable(mm)	length of walls(mm)	Ram stroke(mm)	Opening height(mm)	Amount of ram adj(mm)	Distance of back guage (mm)	Stroke times/min	Throat depth	Main power KW	Net Weight (ton)	Dimension(mm)
30/1300	300	1300	1040	90	300	80	0-400	6-18	170	4	1.8	1300x1300x2000
30/1600	300	1600	1280	90	300	80	0-400	6-18	170	4	2	1600x1300x2000
40/2000	400	2000	1600	120	360	110	0-400	6-18	260	5.5	3.5	2000x1350x2000
40/2200	400	2200	1760	120	360	110	0-400	6-18	260	5.5	3.6	2200x1350x2000
40/2500	400	2500	2000	120	360	110	0-400	6-18	260	5.5	3.8	2500x1350x2000
50/2500	500	2500	2000	120	360	110	0-600	6-18	250	5.5	4	2500x1360x2050
63/2500	630	2500	2000	120	360	110	0-600	6-18	250	7.5	4.9	2500x1480x2050
63/3200	630	3200	2600	120	360	110	0-600	6-18	250	7.5	6.2	3200x1480x2050
63/4000	630	4000	3200	120	360	110	0-600	6-18	250	7.5	6.5	4000x1480x2050
80/2500	800	2500	2000	120	370	110	0-600	6-18	250	11	5.4	2500x1510x2100
80/3200	800	3200	2600	120	370	110	0-600	6-12	250	11	5.9	3200x1550x2100
80/4000	800	4000	3200	120	370	110	0-600	6-12	250	11	7	4000x1550x2100
100/2500	1000	2500	2000	120	380	110	0-600	6-12	320	11	5.9	2500x1560x2200
100/3200	1000	3200	2600	120	380	110	0-600	6-12	320	11	6.9	3200x1560x2260
125/5000	1250	5000	4000	120	380	110	0-600	6-12	320	11	11	5000x1550x2260
100/4000	1000	4000	3200	120	380	110	0-600	6-12	320	11	7.8	4000x1560x2260
125/6000	1250	6000	4800	120	380	110	0-600	4-10	320	11	12.5	6000x1560x2380
160/2500	1600	2500	2000	200	460	190	0-600	6-12	380	11	9	2500x1700x2560
160/3200	1600	3200	2600	200	460	190	0-600	6-12	380	11	10	3200x1700x2560
160/4000	1600	4000	3200	200	460	190	0-600	6-12	380	11	11	4000x1700x2560
160/6000	1600	6000	4800	200	460	190	0-600	4-10	380	11	15.5	6000x1700x2567
200/2500	2000	2500	2000	200	480	190	0-600	6-10	380	18.5	9.8	2500x1760x2570
200/3200	2000	3200	2600	200	480	190	0-600	6-10	380	18.5	10.8	3200x1760x2570
200/4000	2000	4000	3200	200	480	190	0-600	6-10	380	18.5	15.3	4000x1760x2800
200/6000	2000	6000	4800	200	480	190	0-600	4-10	380	18.5	22	6000x1950x2985
250/3200	2500	3200	2600	250	540	240	0-600	4-10	380	18.5	14	3200x1900x3000
250/4000	2500	4000	3200	250	540	240	0-600	4-10	450	18.5	15.5	4000x1900x3000
250/6000	2500	6000	4800	250	540	240	0-600	4-10	450	18.5	24	6000x1950x3140
320/3200	3200	3200	2600	250	560	240	0-600	4-10	450	22	16	3200x1900x3200
320/4000	3200	4000	3200	250	560	240	0-600	4-10	450	22	18.5	4000x1950x3200
320/6000	3200	6000	4800	250	560	240	0-600	4-10	450	22	25	6000x1950x3200
320/8000	3200	8000	6400	250	560	240	0-600	4-10	450	22	31	8000x1950x3450
400/3200	4000	3200	2600	250	560	240	0-600	4-10	450	30	18	3200x1950x3250
400/4000	4000	4000	3200	250	560	240	0-600	4-10	450	30	19.2	4000x1950x3250
400/6000	4000	6000	4800	250	560	240	0-600	4-10	450	30	33	6000x1950x3450
500/4000	5000	4000	3200	250	580	240	0-600	4-10	450	37	24	4000x2050x3620
500/6000	5000	6000	4800	250	580	240	0-600	4-10	450	45	41	6000x2150x3750
500/7000	5000	7000	5600	250	580	240	0-600	4-10	450	45	50	7000x2150x3750
500/8000	5000	8000	6400	250	580	240	0-600	4-10	450	45	60	8000x2150x3800