




PLATE BENDING MACHINE

Model: URM - S 30220



This mechanical model is designed for light medium jobs; it is used in jobs up to 8mm thickness materials. It is used in aluminum bending, Air conditioning channels, Advertising Panels and machine sheet metal cover parts.



STANDARD ACCESSORIES:

- Two rolls powered by single chain and belt driven Helical type gearbox and gear system
- SAE 1050 (CK 45) quality certificate steel rolls with high tensile strength
- Steel welded main frames
- Mechanical manual openable drop-end
- Mobile control panel
- Conical bending device
- Central lubrication system
- Top roll support system
- Precision bending with brake motor
- Motorized adjustment of back roll

TECHNICAL SPECIFICATIONS:

MODEL	USEFULL LENGTH (MM)	PRE-BENDING CAPACITY (MM)	BENDING CAPACITY (MM)	ROOL DIA (MM)	MIN. INTERNATIONAL DIA Ø (MM)	MOTOR POWER (KW)	BACK ROLLS MOTOR (KW)	MACHINE DIMENSION	WEIGHT (KG)
URM-S 10130	1050	5/6	6/7	130	195	2.2	1.1	2750*650*1020	1200
URM-S 10150	1050	6/7	7/8	150	225	3	1.1	2750*680*1040	1450
URM-S 10170	1050	7/8	8/9	170	255	4	1.1	2850*720*1050	1600
URM-S 10190	1050	8/9	9/10	190	285	4	1.5	3200*950*1300	2450
URM-S 15130	1550	4/5	5/6	130	195	2.2	1.1	3250*650*1020	1400
URM-S 15150	1550	5/6	6/7	150	225	3	1.1	3250*680*1040	1650
URM-S 15170	1550	6/7	7/8	170	255	4	1.1	3350*720*1050	1850
URM-S 15190	1550	7/8	8/9	190	285	4	1.5	3700*950*1300	2750
URM-S 20130	2050	2/3	3/4	130	195	2.2	1.1	3750*650*1020	1600
URM-S 20150	2050	¾	4/5	150	225	3	1.1	3750*680*1040	1885
URM-S 20170	2050	4/5	5/6	170	255	4	1.1	3850*720*1050	2100
URM-S 20190	2050	5/6	6/7	190	285	4	1.5	4200*950*1300	3100
URM-S 25150	2550	2/3	3/4	150	225	3	1.1	4250*650*1020	2150
URM-S 25180	2550	3/4	4/5	180	270	4	1.5	4350*950*1300	3050
URM-S 25190	2550	4/5	5/6	190	285	4	1.5	4700*950*1300	3400
URM-S 25220	2550	5/6	6/7	220	330	5.5	2.2	4700*1150*1400	5000
URM-S 30160	3050	1.5/2	2/3	160	240	4	1.1	4850*720*1050	2650
URM-S 30190	3050	2/3	3/4	190	285	4	1.5	5200*950*1300	3750
URM-S 30200	3050	3/4	4/5	200	300	4	1.5	5200*950*1300	4000
URM-S 30220	3050	4/5	5/6	220	330	5.5	2.2	5200*1150*1400	6000